

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: HYBRIFLEX 480

Product code: HYB480

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9OSW

ENGLAND

Tel: 0044 113 240 3456

Fax: 0044 113 240 0024

Email: pault@everbuild.co.uk

1.4. Emergency telephone number

Emergency tel: 0044 113 240 3456 (office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: -: R52/53

Classification under CLP: Skin Sens. 1: H317; Aquatic Chronic 3: H412; -: EUH208

Most important adverse effects: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Label elements under CLP:

Hazard statements: EUH208: Contains n-(2-aminoethyl)-3-aminopropyltrimethoxysilane, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

H317: May cause an allergic skin reaction.

H412: Harmful to aquatic life with long lasting effects.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark



SAFETY DATA SHEET

HYBRIFLEX 480

Page: 2

Precautionary statements: P102: Keep out of reach of children.
P333+313: If skin irritation or rash occurs: Get medical advice.
P261: Avoid breathing vapours.
P103: Read label before use.
P272: Contaminated work clothing should not be allowed out of the workplace.
P302+352: IF ON SKIN: Wash with plenty of soap and water.
P273: Avoid release to the environment.
P280: Wear protective gloves.
P321: Specific treatment (see advice on this label).
P363: Wash contaminated clothing before reuse.
P501: Dispose of contents to hazardous waste.

Label elements under CHIP:

Hazard symbols: Symbol not required.

Risk phrases: R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S29: Do not empty into drains.

Precautionary phrases: Contains n-(2-aminoethyl)-3-aminopropyltrimethoxysilane, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

2.3. Other hazards

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

TRIMETHOXY VINYLSILANE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
220-449-8	2768-02-7	-: R10; Xn: R20	Acute Tox. 4: H332; Flam. Liq. 3: H226	1-10%

MICRONISED WAX

-	-	-: R52	Aquatic Chronic 3: H412	1-10%
---	---	--------	-------------------------	-------

N-(2-AMINOETHYL)-3-AMINOPROPYLTRIMETHOXYSILANE

217-164-6	1760-24-3	Xi: R41; Sens.: R43; Xn: R20; N: R51/53	Eye Dam. 1: H318; Aquatic Chronic 2: H411; Acute Tox. 4: H332; Skin Sens. 1: H317	<1%
-----------	-----------	---	---	-----

[cont...]

SAFETY DATA SHEET

HYBRIFLEX 480

Page: 3

BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE AND METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE.

-	-	Sens.: R43; N: R50/53	Skin Sens. 1: H317; Aquatic Acute 1: H400; Aquatic Chronic 1: H410	<1%
---	---	-----------------------	--	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Wash the spillage site with large amounts of water.

6.4. Reference to other sections

[cont...]

SAFETY DATA SHEET

HYBRIFLEX 480

Page: 4

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: White

Odour: Sweet-smelling

Evaporation rate: Negligible

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Highly viscous

Boiling point/range°C: >150

Flash point°C: >60

Relative density: ~1.4

VOC g/l: 19.1

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

[cont...]

SAFETY DATA SHEET

HYBRIFLEX 480

Page: 5

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE AND METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE.

ORAL	RAT	LD50	3230	mg/kg
------	-----	------	------	-------

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

[cont...]

SAFETY DATA SHEET

HYBRIFLEX 480

Page: 6

12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Deposit into or on to land (e.g. landfill, etc.)

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.
H226: Flammable liquid and vapour.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H332: Harmful if inhaled.
H400: Very toxic to aquatic life.
H410: Very toxic to aquatic life with long lasting effects.
H411: Toxic to aquatic life with long lasting effects.
H412: Harmful to aquatic life with long lasting effects.
R10: Flammable.
R20: Harmful by inhalation.
R41: Risk of serious damage to eyes.
R43: May cause sensitisation by skin contact.
R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

[cont...]

SAFETY DATA SHEET

HYBRIFLEX 480

Page: 7

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52: Harmful to aquatic organisms.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.