

# Technical Data

## SEALANT PRIMER NP2

For Non Porous Surfaces

### Description

EVERBUILD SEALANT PRIMER NP2 is a solvent based, polyorganosiloxane primer for use on Non Porous surfaces prior to applying all common types of silicone, polyurethane and hybrid sealants.

### Benefits

- Works on most common non porous building materials.
- Works with all common silicone types.
- Can also be used with PU and hybrid based sealants.

### Recommended For

- Glass
- uPVC
- Aluminium
- Steel
- Ceramics

### Specific Data

Appearance	Yellow liquid
Odour	Slight
Boiling Point	116-142°C
Flash Point (closed cap)	9°C
Specific Gravity	0.7-0.8
Working Temperature	5 to 40°C
Drying Time @ 20°C	Approx 30 minutes

### Health & Safety

Data sheet available to professional user upon request.

### Application

Apply by brush in one coat and allow to dry.

### Available in

1Ltr tins.

### Storage

Store in cool, dry conditions between +5 and +25°C. Ensure good ventilation. Storage outside these parameters will dramatically reduce shelf life. Opened tins must be closed airtight and used up as soon as possible (within 1 month)

### Shelf Life

12 months from date of manufacture. In original, unopened containers

### Coverage

Coverage will vary according to type and porosity of substrate. As a guide, a 1ltr bottle will cover approx 2.5m<sup>2</sup>.

### Limitations

- Do not use against bitumen or substrates that bleed oil or plasticizers.
- Do not use below +5°C.
- Do not apply to damp or wet surfaces.



*The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.*