

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika Primer 3N

1.2 Relevant identified uses of the substance or mixture and uses advised against

At present there is no complete information available on identified uses. When the data becomes available, it will be integrated into the safety data sheet.

Product use : Pretreatment agent

1.3 Details of the supplier of the safety data sheet

Company : Everbuild Building products LTD
Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds
LS9 OSW
UK

Telephone : 0113 240 3456

E-mail address : sds@everbuild.co.uk

1.4 Emergency telephone number

Emergency telephone number : 0044 113 240 3456 (office hours only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids , Category 2	H225: Highly flammable liquid and vapour.
Eye irritation , Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure , Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

Classification (67/548/EEC, 1999/45/EC)

Highly flammable R11: Highly flammable.

Irritant R36: Irritating to eyes.



R66: Repeated exposure may cause skin dryness

or cracking.

R67: Vapours may cause drowsiness and dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements	:	H225 H319 H336	Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.
Supplemental Hazard Statements	:	EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	Prevention: P210 P233 P261 Response: P303 + P361 + P353 P312 P370 + P378	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a POISON CENTER or doctor/ physician if you feel unwell. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Hazardous components which must be listed on the label:

- 205-500-4 ethyl acetate

Additional Labelling:

EUH208 Contains dibutyltin dilaurate. May produce an allergic reaction.

2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
 This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical Name	Classification	Classification	Concentration
Country GB 000000120488			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika Primer 3N

Revision Date 12.03.2015

Version 1.2

Print Date 12.03.2015



CAS-No. EC-No. Registration number	(67/548/EEC)	(REGULATION (EC) No 1272/2008)	[%]
ethyl acetate 141-78-6 205-500-4 01-2119475103-46-XXXX	F; R11 Xi; R36 R66 R67	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336	>= 50 - <= 100
xylene 1330-20-7 215-535-7 01-2119488216-32-XXXX	R10 Xn; R20/21 Xi; R38	Asp. Tox.1; H304 Flam. Liq.3; H226 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315	>= 5 - < 10
isopropanol 67-63-0 200-661-7 01-2119457558-25-XXXX	F; R11 Xi; R36 R67	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336	>= 5 - < 10
ethylbenzene 100-41-4 202-849-4 01-2119489370-35-XXXX	F; R11 Xn; R20-R48/20- R65	Flam. Liq.2; H225 Acute Tox.4; H332	>= 1 - < 2,5
methanol 67-56-1 200-659-6 01-2119433307-44-XXXX	F; R11 T; R23/24/25- R39/23/24/25	Flam. Liq.2; H225 Acute Tox.3; H331 Acute Tox.3; H311 Acute Tox.3; H301 STOT SE1; H370 STOT SE1; H370 STOT SE1; H370	< 1
dibutyltin dilaurate 77-58-7 201-039-8 01-2119496068-27-XXXX	Repr.Cat.2; R60 Repr.Cat.2; R61 Mut.Cat.3; R68 T; R48/25 N; R50/53 C; R34 R43	Skin Corr.1C; H314 Skin Sens.1; H317 Muta.2; H341 Repr.1B; H360FD STOT SE1; H370 STOT RE1; H372 Aquatic Acute1; H400 Aquatic Chronic1; H410	>= 0,1 - < 0,25

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika Primer 3N

Revision Date 12.03.2015

Version 1.2



Print Date 12.03.2015

- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Excessive lachrymation
Erythema
Loss of balance
Vertigo
See Section 11 for more detailed information on health effects and symptoms.

- Risks : irritant effects

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO₂), Dry chemical
- Unsuitable extinguishing media : Water

5.2 Special hazards arising from the substance or mixture

- Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters *	Basis *
ethyl acetate	141-78-6	TWA	200 ppm	GB EH40
		STEL	400 ppm	GB EH40
xylene	1330-20-7	TWA	50 ppm 220 mg/m3	GB EH40
		STEL	100 ppm 441 mg/m3	GB EH40
		TWA	50 ppm 221 mg/m3	2000/39/EC
		STEL	100 ppm 442 mg/m3	2000/39/EC
		TWA	400 ppm 999 mg/m3	GB EH40
isopropanol	67-63-0	TWA	400 ppm 999 mg/m3	GB EH40
		STEL	500 ppm 1.250 mg/m3	GB EH40
ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m3	2000/39/EC
		STEL	200 ppm 884 mg/m3	2000/39/EC
		TWA	100 ppm 441 mg/m3	GB EH40
		STEL	125 ppm 552 mg/m3	GB EH40
methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC
		TWA	200 ppm 266 mg/m3	GB EH40
		STEL	250 ppm 333 mg/m3	GB EH40
dibutyltin dilaurate	77-58-7	TWA	0,1 mg/m3	GB EH40
		STEL	0,2 mg/m3	GB EH40

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika Primer 3N

Revision Date 12.03.2015

Version 1.2



Print Date 12.03.2015

methanol : End Use: Workers
Exposure routes: Skin contact
Exposure time: 8 h
Value: 40 mg/m³

End Use: Consumers
Exposure routes: Skin contact
Exposure time: 8 h
Value: 260 mg/m³

PNEC

methanol

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields
Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (0,4 mm),
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Environmental exposure controls

General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: colourless
Odour	: very faint
Odour Threshold	: No data available
Flash point	: ca. -4 °C
Ignition temperature	: 465 °C
Lower explosion limit (Vol%)	: 1 %(V)
Upper explosion limit (Vol%)	: 7 %(V)
Flammability (solid, gas)	: No data available
Oxidizing properties	: No data available
Auto-ignition temperature	: No data available
pH	: No data available
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Vapour pressure	: 99,9915 hPa
Density	: ca.0,98 g/cm ³ at 20 °C
Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 7 mm ² /s at 40 °C
Relative vapour density	: No data available
Evaporation rate	: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

xylene:

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg
Method: Converted acute toxicity point estimate

methanol:

Acute oral toxicity : Acute toxicity estimate: 100 mg/kg
Method: Converted acute toxicity point estimate

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Converted acute toxicity point estimate

Acute dermal toxicity : Acute toxicity estimate: 300 mg/kg
Method: Converted acute toxicity point estimate

dibutyltin dilaurate:

Acute oral toxicity : LD50 Oral (Rat): 2.071 mg/kg

Skin corrosion/irritation

Product:

Remarks: Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Product:

Remarks: Causes serious eye irritation.

Respiratory or skin sensitisation

Product:

Remarks: No data available

Germ cell mutagenicity

Product:

Germ cell mutagenicity- Assessment : No data available

Carcinogenicity

Product:

Carcinogenicity - Assessment : No data available

Reproductive toxicity

Product:

Reproductive toxicity - Assessment : No data available

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

dibutyltin dilaurate :

Toxicity to fish : LC50: 3,1 mg/l, 96 h, Fish

Toxicity to daphnia and other aquatic invertebrates : EC50: 1 mg/l, 48 h, Daphnia (water flea)

Toxicity to algae : EC50: 1 - 10 mg/l, 72 h, Selenastrum capricornutum (green)

algae)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- European Waste Catalogue : 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances
- Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

ADR

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika Primer 3N

Revision Date 12.03.2015

Version 1.2



Print Date 12.03.2015

14.1 UN number : 1866
14.2 Description of the goods : RESIN SOLUTION
14.3 Class : 3
14.4 Packing group : II
Classification Code : F1
Labels : 3
Tunnel restriction code : (D/E)
14.5 Environmentally hazardous : no

IATA

14.1 UN number : 1866
14.2 Description of the goods : Resin solution
14.3 Class : 3
14.4 Packing group : II
Labels : 3
14.5 Environmentally hazardous : no

IMDG

14.1 UN number : 1866
14.2 Description of the goods : RESIN SOLUTION
14.3 Class : 3
14.4 Packing group : II
Labels : 3
EmS Number 1 : F-E
EmS Number 2 : S-E
14.5 Marine pollutant : no

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Labelling according to EC Directives (1999/45/EC)

Hazard pictograms :



Highly flammable



Irritant

R-phrases) : R11 R36 R66 R67
Highly flammable.
Irritating to eyes.
Repeated exposure may cause skin dryness or cracking.
Vapours may cause drowsiness and dizziness.

ness.

Sensitising components : dibutyltin dilaurate
May produce an allergic reaction.

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (= > 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH Information: All substances contained in our Products are
- preregistered or registered by our upstream suppliers, and/or
- preregistered or registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

VOC-CH (VOCV) : 66,34 %

VOC-EU (solvent) : 66,34 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002
Control of Substances Hazardous to Health Regulations 2002
The Management of Health and Safety at Work Regulations 1999
Health and Safety at Work Act 1974
Environmental Protection Act 1990 & Subsidiary Regulations

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of R-Phrases

R10 Flammable.
R11 Highly flammable.
R20 Harmful by inhalation.
R20/21 Harmful by inhalation and in contact with skin.
R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika Primer 3N

Revision Date 12.03.2015

Version 1.2



Print Date 12.03.2015

R34	Causes burns.
R36	Irritating to eyes.
R38	Irritating to skin.
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R43	May cause sensitisation by skin contact.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R48/25	Toxic: danger of serious damage to health by prolonged exposure if swallowed.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R60	May impair fertility.
R61	May cause harm to the unborn child.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.
R68	Possible risk of irreversible effects.

Full text of H-Statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H360FD	May damage fertility. May damage the unborn child.
H370	Causes damage to organs if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure if swallowed.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
Muta.	Germ cell mutagenicity
Repr.	Reproductive toxicity
Skin Corr.	Skin corrosion
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation
STOT RE	Specific target organ toxicity - repeated exposure

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006

Sika Primer 3N

Revision Date 12.03.2015

Version 1.2

Print Date 12.03.2015



STOT SE Specific target organ toxicity - single exposure

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any any use and processing.

|| Changes as compared to previous version !